



**Test Results for high/Flash fire:**

Parallel Position Clearance Distance	Position	Clearance (mm)	Max temp rise (°C)		
			High	Flash	
	(A) Rear	100	Rear Wall		
			53.04	59.64	
	(B) Side	250	Side Wall		
			61.49	62.77	
	(C) Floor protector (front)	300	Floor		
			15.78	17.74	
	(D) Floor protector (side)	200	Ceiling		
			23.63	26.01	

Corner Position Clearance Distance	Position	Clearance (mm)	Max temp rise (°C)		
			High	Flash	
	(F) Side	120	Rear Wall		
			43.12	38.89	
	(G) Side	120	Side Wall		
			42.42	39.18	
	(H) Floor protector (front)	300	Floor		
			19.08	20.00	
	(I) Floor protector (side)	200	Ceiling		
			25.64	23.92	

\* Note that this temperature passed within the laboratories margin of uncertainty.

**Technical Note:**

1. The clearance measurement A, B, F and J were taken from the distance between walls and closest point of the appliance, C and H was measured from the front of the fuel-loading opening to the edge of the floor protector, D and I was measured from each side of fuel-loading opening.
2. The flue was installed onto the flue spigot, extended centrally and vertically without bend before and after penetration of the ceiling plane.
3. Drawings shown above are not to scale.